

Version	2.0	Date	11/3/21
Prepared By	JC		


PRODUCT SPECIFICATION			
Category	Commercial Strip		
Item Number	9578		
Stock Code	FXCSL68SW/96FR/8CCT3/MV		
Mounting	Surface Mount		
Housing Color	White		
PICTURE			

ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	44 / 58 / 68	Replacement Wattage (W)	5 x 32W T8
Tested Wattage (W)	44 / 58 / 68		
Input Voltage (V)	120-277V		
Voltage Frequency (Hz)	50/60	Surge Protect Level	2KV
Input Current (A)	0.62 (max)	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	6,248 7,540 9,398	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	138	Beam Angle (°)	Flood
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-13°F ~ 104°
Storage Temperature (°F)	-13°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10438	SEN-HB001VCR-1	Motion Sensor
P10323	SEN-HD06R	Remote Programmer for P10438
P10011	WG-2.5CSL/48/WH	WireGuard (x2pcs required for 8ft)
7334	BAEM15-48BC/MV-A	15W Emergency Driver

PRODUCT DIMENSIONS			
Length- in / (mm)	92.82" 2358		
Height- in / (mm)	2.71" 69		
Depth- in / (mm)	2.58" 66		
IK Rating	-		
Weight (lbs)	9.92		
Mounting Height (ft)	10~25		
Cable Length (ft)	-		

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS